



Board Type

FR MDF

Fire Retardant medium density fibreboard (MDF), for use in locations where improved performance in reaction to fire is required.

- Product available with design double sided.
- Real wood veneer (textured or smooth).
- Eco-friendly paint and varnish with UV curing. Low percentage of VOC's.
- Standard or high gloss varnish.
- Applications: Wall and ceiling panels, partitioning. Suitable to hotel and leisure sector, medical and services.

Technical Features

Dimensions	2420x1200. Others upon request.
Thickness	12, 16 and 19mm
Density	820 kg/m ³ (± 30 kg/m ³), according to EN 323.
Dimensional Tolerances (length/width)	± 2mm, according to EN 324-1 standard.
Formaldehyde Content	Low emission of formaldehyde, Class E1.
Reaction to fire	B-s2,d0 according to EN13501-1

April 2017

Notes: Vicaima assumes, unless advised otherwise, that the customer is the holder of the copyright, patent design, design registration or any other industrial property right related to the images supplied to Vicaima.

www.vicaima.com

United Kingdom

Vicaima Ltd
Marlowe Avenue – Greenbridge Ind. Est.
Swindon. Wiltshire SN3 3JF
Tel: +44 01793 532333 | E-mail: info@vicaima.com



Other Countries

Vicaima Indústria de Madeiras e Derivados, S.A.
Apartado 9, 3730-953
Vale de Cambra, Portugal
Tel: +351 256 426 300 | E-mail: vicaima@vicaima.com

