



## Board Type

### MDF

Medium density fibreboard (MDF) for use in dry environments.

- Product available with design double sided.
- Real wood veneer (textured or smooth), foil or primed.
- Eco-friendly paint and varnish with UV curing. Low percentage of VOC's.
- Standard or high gloss varnish.
- Applications: Furniture, kitchen modules, wall and ceiling panels, packaging and shop fitting.

### Technical Features

Dimensions	2420x1200. Others upon request.
Thickness	5, 12, 16 and 19mm
Density	Between 820 and 700 kg/m <sup>3</sup> ( $\pm$ 30 kg/m <sup>3</sup> ), depending on thickness. According to EN 323 standard.
Dimensional Tolerances (length/width)	$\pm$ 2mm, according to EN 324-1 standard.
Formaldehyde Content	Low emission of formaldehyde, Class E1.

April 2017

**Notes:** Vicaima assumes, unless advised otherwise, that the customer is the holder of the copyright, patent design, design registration or any other industrial property right related to the images supplied to Vicaima.

[www.vicaima.com](http://www.vicaima.com)

#### United Kingdom

Vicaima Ltd  
Marlowe Avenue – Greenbridge Ind. Est.  
Swindon. Wiltshire SN3 3JF  
Tel: +44 01793 532333 | E-mail: [info@vicaima.com](mailto:info@vicaima.com)



#### Other Countries

Vicaima Indústria de Madeiras e Derivados, S.A.  
Apartado 9, 3730-953  
Vale de Cambra, Portugal  
Tel: +351 256 426 300 | E-mail: [vicaima@vicaima.com](mailto:vicaima@vicaima.com)

